PHP9030DJ

GE Profile™ 30″ Built-In Touch-Control Induction Cooktop


DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

IMPORTANT: Requires a 3″ free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15″ minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48″ flexible armored cable.


NOTE: 30″ induction cooktops are approved for use over select GE 27″ and GE 30″ Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2” minimum flat countertop surface and 25” minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered. **Before installing, consult installation instructions packed with product for current dimensional data.**

CUTOUT FILLER TRIM KIT: A filler trim kit is available for use if your countertop cutout is larger than the dimension shown, up to 29-13/16″ x 20-7/16″. Order JXTR32B for black or JXTR32W for white, to reduce the cutout opening for installation of this cooktop. These kits may be ordered from your GE Appliances Dealer.


APPROXIMATE COOKING DIMENSIONS



To insure accuracy, it is best to make a template when cutting the opening in the counter



INSTALLATION ABOVE A WALL OVEN



KW RATING	
240V	7.4
208V	6.4
AMPERAGE	
240V	40 Amps†
208V	40 Amps†

†**NOTE:** Check local codes for required breaker size.

GE APPLIANCES

For answers to your Monogram, GE Café™ Series, GE Profile™ Series or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service, 800.626.2000.

GE APPLIANCES FIT GUARANTEE

ADA COMPLIANT

UL® Listed by Underwriters Laboratories

Specification Revised 03/23

PHP9030DJ

GE Profile™ 30″ Built-In Touch-Control Induction Cooktop

FEATURES AND BENEFITS

Four induction elements

Digital touch controls

Power Boil (11″ 3,700-watt induction element)

SyncBurners

Auto-pan size detection

Worry-free pan detection

Kitchen timer


Control lock capability

Red LED with black glass surface and stainless trim

Hot surface indicator lights

Fit Guarantee

Model PHP9030DJBB – Black on black



GUARANTEED FIT

Replacing a similar cooktop from GE Appliances or another brand? GE cooktops are guaranteed for an exact fit or GE Appliances will pay up to $100 toward modifications

Visit geappliances.com for more info

GE APPLIANCES