

Color Variants

WS261710 Stainless steel-backed glass front 24" (60 cm), height 5 1/2"

WS261710

200 series warming drawer

Stainless steel-backed glass front

24" (60 cm), height 5 1/2"

- Hygienic interior with stainless steel and glass.
- Temperature range from 100° F -175° F.
- Keeps food and drinks warm or finishes a roast.

Capacity

Net volume 0.75 cu.ft. Interior dimensions: H 3 3/4" x W 18 11/16" x D 18 3/16"

Max. load 55 lbs.

Coffee set for ten: espresso cups, cappuccino cups and plates, or place setting for six, including 11" plates and

Additional bowls and serving dishes depending on size.

Features

Four temperature levels. Integrated base plate heating. Convection fan for even heat distribution. Operation indication. Rotary knob operation. Stainless steel interior. Removable handle. Drawer pull at the front bottom center

of the drawer. Cushioned closing system

Planning notes

The front of the appliance extends 1 7/8" from the cabinet front. Mount BO/BS 200 or CM 210 directly on top of the warming drawer without a partition shelf in between. The power outlet can be planned

behind the appliance.

Connecting cable 6" with plug.

Rating

Total rating: 0.81 kW. Total Amps: 10 A 120 V / 60 Hz

Product Features

Power output heating

0.810

Power Level

high, low, medium, plate

Type of control rotating switch

Temperature control

electronic Time control

Consumption and connection features

UPC code

825225872627

Product color Stainless steel

Alternative colors available

Watts (W)

810

Current (A) 10

Volts (V)

120

Frequency (Hz)

Approval certificates

CSA

Power cord length (in)

Plug type

120V-3 prong Required cutout size (HxWxD) (in)

5 1/2 " x 22 1/16 " x 21 5/8 '

Overall appliance dimensions (HxWxD)

5 1/2 " x 23 3/8 " x 20 1/2 "

Product packaging dimensions

(HxWxD) (in) 8.07 x 25.78 x 28.93

Net weight (lbs)

Gross weight (lbs) 49

2013-04-22

Page 1



WS261710 200 series warming drawer Stainless steel-backed glass front 24" (60 cm), height 5 1/2"

2013-04-22 Page 2

Installation with CM 210



