

DEU2450CI



FEATURES

- Fully customizable exterior—accepts custom panels for an integrated look within cabinetry or stainless-steel accessory panels and handles to coordinate with other Sub-Zero, Wolf, and Cove appliances
- Seamlessly integrating anywhere, undercounter refrigeration adds comfort to your master suite, creates a corner for libations in the study—the options are endless
- On-door shelf easily accommodates a wide variety of condiments and beverages, with ample room for larger two-liter bottles
- Stores fresh ice in a removable freezer storage bin, and yields extra cubes with Max Ice Mode
- Intuitive, on-door touch control panel offers ergonomic, convenient access to settings
- Cleanup is simple with nano-coated, spillproof shelf
- Offers precise temperature control within one degree of setpoint, preserving dairy, produce, craft beer, and other perishables at their optimal temperature
- Soft-on LED lighting fully illuminates the interior when the door is open
- Our convenient Owner's App allows you to adjust temperatures and Max Ice Mode, be notified of a door left ajar, or receive remote service diagnostics


ACCESSORIES

- Custom Panel Lock Kit
- Dual Install Kit - Handle-to-Drawer
- Dual Install Kit - Handle-to-Handle
- Outdoor Stainless Steel Solid Door Panel With Lock - Pro Handle, Left Hinge
- Outdoor Stainless Steel Solid Door Panel With Lock - Pro Handle, Right Hinge
- Pro Handle
- Tubular Handle
- Stainless Steel Solid Door Panels
- Stainless Steel Dual Kickplates

Accessories are available through an authorized dealer. For local dealer information, visit subzero-wolf.com/locator.



HANDLE ACCESSORIES



PRODUCT DETAILS

REFRIGERATOR

- One stationary and one adjustable shelf
- One on-door shelf


FREEZER

- Removable ice storage bin


PRODUCT SPECIFICATIONS

Model	DEU2450CI
Dimensions	24"W x 34 1/2"H x 23 1/8"D
Refrigerator Capacity	3.0 cu. ft.
Freezer Capacity	1.7 cu. ft.
Weight	134 lbs
Electrical Supply	115 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Plumbing Supply	1/4" OD copper, braided stainless steel or PEX tubing
Plumbing Pressure	35-120 psi
Receptacle	3-prong grounding-type

ELECTRICAL



PLUMBING




NOTE: The electrical outlet must be positioned with the grounding prong to the right of the thinner blades.

PANEL SPECIFICATIONS For complete panels specifications including width/height, weight requirements and thickness requirements visit subzero-wolf.com/reveal.


NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

INTERIOR VIEW




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.


DIMENSIONS



HEIGHT DIMENSIONS ± 1/2" (13)



STANDARD INSTALLATION



NOTE: 3 1/2" (89) finished returns will be visible and should be finished to match cabinetry.

