## 26.2 cu. ft. French Door Refrigerator



- 26.2 cu. ft. Capacity
- Slim SpacePlus® Ice System
- Dual Ice Maker
- Smart Cooling® System
- Door Cooling +
- LED Lighting
- LoDecibel<sup>™</sup> Quiet Operation
- LG ThinQ® Technology (Wi-Fi)





COLOR AVAILABILITY		
LFXS26973S – PrintProof™ Stainless Steel		
LFXS26973D – PrintProof™ Black Stainless Steel		
CAPACITY		
Refrigerator (cu. ft.)	17.4	
Freezer (cu. ft.)	8.8	
Total Capacity (cu. ft.)	26.2	
ENERGY		
Energy Consumption (kWh / Year)	686	
ENERGY STAR® Qualified	Yes	
WATER & ICE SYSTEM		
Ice & Water Dispenser	Yes	
Dispenser Type	Integrated Tall Ice & Water	
Measured Fill	No	
Dual Ice Maker	Yes	
Ice System	Slim SpacePlus®	
Daily Ice Production	6.0 lbs.	
IcePlus <sup>™</sup> Production	6.5 lbs.	
Ice Storage Capacity	2.5 lbs. + 4.0 lbs.	
Dispenser Light	Yes	
Water Filter	LT1000P (NSF-Certified*)	
COOLING		
Compressor Type	Linear Compressor	
Dual Evaporators	No	
Cooling System	Smart Cooling®	
Multi-Air Flow <sup>™</sup> System	Yes	
Door Cooling+	Yes	
Temperature Sensors	6	
Fresh Air Filter	Yes	
	'	


CONVENIENCE	
Display Type	Membrane / White LED
Temperature Controls	Electronic / Digital
Door Alarm	Yes
Child Lock	Yes
Auto Closing Door Hinge	Yes
ADA Compliant	No
Sabbath Mode	Yes (Star-K-Certified)
LoDecibel™ Quiet Operation	Yes
REFRIGERATOR	
No. of Shelves	5 (4 Split)
Cantilevered Shelves	Hybrid Cantilevered
Shelf Construction	Spill Protector <sup>™</sup> Tempered Glass
Crisper Bins	2 Humidity Crispers
Glide N' Serve <sup>™</sup> Pantry Drawer	Yes
Cool Guard	No
Refrigerator Light	Ceiling LED
REFRIGERATOR DOOR	
InstaView <sup>™</sup> Door-in-Door <sup>®</sup>	No
Door-in-Door® with ColdSaver™ Panel	No
No. of Door Bins	6 Total (2 Adjustable Gallon Sized)
Door Bin Construction	1 Piece (Clear)
FREEZER	
Freezer Type	Pull Drawer
Freezer Drawers	2-Tier Organization
DuraBase <sup>™</sup> Solid Drawer Base	Yes
Drawer Divider	Yes
Ice Storage	Ice Maker & Ice Bin in Freezer
Freezer Light	LED Lighting
Freezer Handle	SmartPull™ Handle


SMART FEATURES	
Wi-Fi Enabled	Yes
ThinQ <sup>®</sup>	Yes
Proactive Customer Care	Yes
Voice Control	Google Assistant, Amazon Alexa
SmartDiagnosis <sup>™</sup>	Yes
Remote Monitoring	Yes
MATERIALS AND FINISHES	
Hidden Hinges	Yes
Surface	Smooth
Fingerprint & Smudge Resistant Exterior	Yes
Handles	Matching Handles
ACCESSORIES	
Replacement Water Filter	LT1000P
Replacement Fresh Air Filter	LT120F
TECHNICAL SPECS	
Required Power Supply	115 V, 60 Hz, 15 Amp
Plug Type	3-Prong
Power Cord Location	Back
Min. / Max. Water Pressure	20 – 120 psi
DIMENSIONS / CLEARANCES / V	VEIGHTS
Depth with Handles	34 <b>7</b> /8"
Depth without Handles	32 <b>3</b> / <b>8</b> "
Depth without Door	28 1/2"
Depth (Total with Door Open)	47 1/ <b>4</b> "
Height to Top of Case	68 1/ <sub>2</sub> "
Height to Top of Door Hinge	69 <b>3</b> / <b>4</b> "
Width	35 <b>3</b> / <b>4</b> "
Width (Door Open 90° with Handle)	44 1/4"
Width (Door Open 90° without Handle)	39 1/ <b>4</b> "
Door Edge Clearance with Handle	4 1/2"
Door Edge Clearance without Handle	1 1/3"
Installation Clearance	Sides 1/8", Top 1", Back 2"
Approx. Weight (Product / Carton)	284 lbs. / 316lbs.
Carton Dimensions (WxHxD)	38" x 73" x 36"
LIMITED WARRANTY	
Parts & Labor	1 Year
Sealed System (Parts & Labor)	5 Years
Compressor (Parts & Labor)	5 Years
Linear / Inverter Compressor (Parts Only)	10 Years



\*System tested and certified by NSF® International against NSF / ANSI Standard 42, Standard 53 and Standard 401.

## **DIMENSIONS / CLEARANCES**





DIMENSIONS / CLEARANCES		
Α	Depth without Handle	32 <b>3</b> / <b>8</b> " (822 mm)
В	Width	35 3/ <sub>4</sub> " (908 mm)
С	Height to Top of Case	68 <sup>1</sup> / <sub>2</sub> " (1740 mm)
D	Height to Top of Hinge	69 <b>3</b> / <b>4</b> " (1772 mm)
Е	Back Clearance	2" (50 mm)
F	Depth without Door	28 <sup>1</sup> / <sub>2</sub> " (724 mm)
G	Depth with Handle	34 <b>7</b> / <b>8</b> " (886 mm)
Н	Depth (Total with Freezer Drawer Open)	56 1/ <sub>4</sub> " (1426 mm)
I	Depth (Total with Door Open 90°)	47 <b>1</b> / <b>4</b> " (1199 mm)

## **INSTALLATION NOTES**

- The installation location chosen for the refrigerator should allow space behind the unit for connections and airflow and space in front to open the doors and drawers.
- Too small of a distance from adjacent items may result in lowered freezing capability and increased electricity consumption charges. Allow at least 24 inches (610 mm) in front of the refrigerator to open the doors, and at least 2 inches (50.8 mm) between the back of the refrigerator and the wall.

